

Cherry Tree

Commercial & Industrial Laundry Solutions



GZZ & GDZ Range Automatic Dryers

The GZZ and GDZ range of tumble dryers are designed to meet the demands of any busy laundry environment. Energy efficient, low maintenance, easy to use, compact in design and of quality build.

Excellent finishing results are produced across a wide range of materials and work categories. The range is available in steam or electric heating formats.

The GZZ & GDZ Range is available in the following sizes:

15 Kgs / 33 Lbs. 25 Kgs / 55 Lbs.
50 Kgs / 110 Lbs. 100 Kgs / 220 Lbs

FEATURES:

MICROPROCESSOR CONTROLLED

- User friendly operator controls.
- Process flexibility through microprocessor programmes.
- Control of drying process.

HIGH EFFICIENCY DRYING PROCESS

- Reversing action to suit fabric type.

COMPACT QUALITY CONSTRUCTION

- Corrosion resistant stainless steel elements ensures hygienic long life performance.
- Compact design with ease of access for maintenance.
- Manufactured to ISO 9001:2008 Quality Standard.
- Built to safety standards in line with UK and EU legislation.



Cherry Tree Machines Ltd.
Imperial House, Gorse Street.
Blackburn, Lancashire.
United Kingdom. BB1 3EU

Tel: 01254 671155
Fax: 01254 671144

Web: www.cherrytreemachines.co.uk
E-mail: enquiries@cherrytreemachines.co.uk

GZZ & GDZ RANGE

Automatic Dryers



| MODEL | UNITS | GZZ-15 / GDZ-15 | GZZ-25 / GDZ-25 | GZZ-50 / GDZ-50 | GZZ-100 / GDZ-100 |
|------------------------------------|----------------|-----------------|-----------------|-----------------|-------------------|
| Capacity | Kgs. / lbs. | 15kgs / 33lbs. | 25kgs / 55lbs. | 50kgs / 110lbs. | 100kgs / 220lbs. |
| Size – Length | mm | 1080 | 1270 | 1500 | 1930 |
| - Width | mm | 870 | 1023 | 1265 | 1610 |
| - Height | mm | 1450 | 1750 | 2185 | 2420 |
| Drum Diameter | mm | ø780 | ø930 | ø1200 | ø1600 |
| Drum length | mm | 650 | 800 | 1000 | 1100 |
| Drum volume | m ³ | 0.295 | 0.53 | 1.11 | 2.11 |
| Door diameter | mm | ø650 | ø650 | ø800 | ø800 |
| Loading height | mm | 720 | 735 | 920 | 920 |
| Electric heating power consumption | Kw / cycle | 9 | 15 | 29 | — |
| Steam heating consumption | Kgs / cycle | 18—25 | 25—30 | 80—90 | 160—180 |
| Steam pressure | Bar | 5—6 (6 Max) | | | |
| Drum speed | rpm | 45 | 35 | 32 | 29 |
| Cage motor | Kw | 0.55 | 0.75 | 1.5 | 3 |
| Fan motor | Kw | 0.37 | 0.75 | 1.5 | 2.5 |
| Electrical power | V / Ph / Hz | 400 / 3 / 50 | | | |
| Electrical power consumption | Kw / cycle | 0.5 | 0.9 | 1.8 | 3.5 |
| Steam inlet size | BSP | 1" BSP | 1" BSP | 1" BSP | 1" BSP |
| Steam outlet | BSP | ¾" BSP | ¾" BSP | ¾" BSP | 1" BSP |
| Outlet vent | mm | 170 x 170 | 230 x 270 | 270 x 350 | 330 x 400 |
| Net weight | Kgs | 350 | 700 | 800 | 1500 |
| Shipping weight | Kgs | 400 | 840 | 920 | 1660 |
| Shipping volume | m ³ | 1.50 | 2.50 | 4.56 | 7.60 |

Note: GZZ model is steam heated and GDZ model is electrically heated

We reserve the right to amend specifications without notice.
© Cherry Tree Machines Ltd.



Cherry Tree Machines Ltd.
Imperial House, Gorse Street,
Blackburn, Lancashire,
United Kingdom. BB1 3EU

Tel: 01254 671155
Fax: 01254 671144

Web: www.cherrytreemachines.co.uk
E-mail: enquiries@cherrytreemachines.co.uk