

SF RANGE TUMBLE DRYERS

SC Drying Tumblers

Available in the following sizes:

70 Kgs. (154 Lbs) 150 Kgs (330 Lbs) 200 Kgs (440 Lbs) 280 Kgs (616Lbs)

FEATURES:

- Stainless Steel Drum AISI-304.
- Front loading with rear unload.
- Automatic reverse tumble action
- Designed for operator safety to current UK and European requirements.
- High level of dependability of operation.
- Simple to operate.
- High operating efficiency
- Compact and robust design.
- Easy access for maintenance.



SF Drying Tumblers

Available in the following sizes:

85 Kgs. (187 Lbs) 150 Kgs (330 Lbs) 200 Kgs (440 Lbs) 300 Kgs (660Lbs)

FEATURES:

- Stainless Steel Drum AISI-304.
- Front loading and front automatic tilting unloading.
- Automatic reverse tumble action
- Designed for operator safety to current UK and European requirements.
- High level of dependability of operation.
- Simple to operate.
- High operating efficiency
- Compact and robust design.
- Easy access for maintenance.



Cherry Tree Machines Ltd.

Imperial House, Gorse Street,
Blackburn, Lancashire.
United Kingdom. BB1 3EU

Tel: 01254 671155

Fax: 01254 671144

Web: www.cherrytreemachines.co.uk

Email: enquiries@cherrytreemachines.co.uk

Cherry Tree

Commercial & Industrial Laundry Solutions



SF Range Dryers

Tilting Tumble Dryers

Model	Units	SF-80V	SF-125V	SF-200V	SF-300V
Capacity	Kgs/lbs	80 / 176	125 / 275	200 / 440	300 / 660
Approx Drying Time	Mins	35	35	35	35
Size – Length	mm	1720	2120	2650	3120
- Width	mm	2050	2200	2775	2970
- Height	mm	2830	3020	3225	3620
Tilted Length	mm	2170	2570	3100	4100
Tilted Height	mm	3280	3260	3680	4079
Unload forward tilt angle	Deg	15°			
Drum Diameter	mm	1500	1500	1900	1900
Drum length	mm	1022	1422	1424	1924
Drum volume	M ³	1.806	2.512	4.04	5.455
Door diameter	mm	880	880	950	950
Loading height	mm	1030	1030	1450	1450
Steam pressure	bar	6- 9 (9 Max)			
Steam consumption	Kg/cycle	150—200	200—400	400—600	600—800
Cage motor size	Kw	1.5	2.2	5.5	7.5
Fan motor size	Kw	4	4	2 off 4	2 off 11
Electrical power	V/Ph/Hz	400V // 3Ph / 50Hz			
Steam inlet size	BSP	1 1/4"	1 1/2"	1 1/2"	1 1/2"
Steam condensate	BSP	1"	1"	1"	1"
Outlet vent	mm	330 x 550	330 x 550	2 off 280 x 470	Off 280 x 470
Net weight	Kgs	1950	2500	3850	4600
Shipping weight	Kgs	2200	2800	4235	5060
Shipping volume	Cu. M	10.65	14.43	21.81	32.08

We reserve the right to amend specifications without notice.
© Cherry Tree Machines Ltd.

Equipment - Remanufactured equipment - Maintenance support - Spares & accessories

Cherry Tree



Cherry Tree
Commercial & Industrial Laundry Solutions



Cherry Tree Machines Ltd.
Imperial House, Gorse Street,
Blackburn, Lancashire,
United Kingdom. BB1 3EU

Tel: 01254 671155
Fax: 01254 671144

Web: www.cherrytreemachines.co.uk
E-mail: enquiries@cherrytreemachines.co.uk

SC Range

Through Put Tumble Dryers

Model	Units	SC-70V	SC-150V	SC-200V	SC-300V
Capacity	Kgs/lbs	70 / 154	150 / 330	200 / 440	300 / 660
Approx Drying Time	Mins	35	30	40	40
Size – Length	mm	2450	3200	3700	3600
- Width	mm	1905	1905	1905	2300
- Height	mm	4030	4030	4030	4060
Drum Diameter	mm	1480	1480	1480	1900
Drum length	mm	1000	1800	2300	1800
Drum volume	M ³	1.897	3.09	3.95	5.39
Steam pressure	bar	6- 8 (8 Max)			
Steam consumption	Kg/cycle	200	250	400	600
Cage motor size	Kw	2.2	4	5.5	11
Fan motor size	Kw	11	15	15	15
Electrical power	V/Ph/Hz	400V // 3Ph / 50Hz			
Steam inlet size	BSP	1 1/2"	1 1/2"	1 1/2"	1 1/2"
Steam condensate	BSP	1"	1"	1"	1 1/4"
Outlet vent	mm	454 x 314	454 x 314	454 x 314	500 x 630
Net weight	Kgs	2250	2600	3100	4000
Shipping weight	Kgs	2415	3120	3575	4400
Shipping volume	Cu. M	7.8	16.34	18.8	24.03

We reserve the right to amend specifications without notice.
© Cherry Tree Machines Ltd.

