

Tumble dryer

T4190

Features and benefits

- Compass Control microprocessor
 - One knob operation for Program Selection and Start
 - Language selection
 - Large and clear display
- High productivity – 2 full loads per hour
- Low energy consumption for optimal efficiency
- Selection of temperature and time for easy operation
- Reversible door hanging for a convenient laundry flow
- Easy access to vital parts from front and rear for simple servicing
- Serviceprogram for adjustment of 20 parameters eg. temperature and cool-down time

Main options

- Residual Moisture Control for an accurate drying result and a low energy consumption
- Reversing drum for less tangling of large items
- Stainless steel front
- Stainless steel drum
- Payment: coin-meter, chipcard reader, CP connection
- Stainless steel base frame
- Separate condense system
- Fresh air intake



Main specifications		T4190			
Rated capacity, filling factor 1:18	kg/lb	10.6/23			
filling factor 1:25	kg/lb	7.6/17			
Drum volume	litre	190			
Drum diameter	mm	680			
Heating, electric	kW	6/8			
gas	BTU/h (kW)	20500/27300 (6/8)			
Consumption data*		6kW	8kW	Gas 6 kW	Gas 8 kW
Total time full load	min	35	27	36	29
Energy consumption full load	kWh	3.45	3.53	3.67	3.74
Evaporation	g/min	102	129	106	131
Energy kWh/litre water evaporated	kWh/l	0.92	0.94	–	–
Energy BTU/litre water evaporated	BTU/l	–	–	3296	3359

* At rated capacity 100% cotton load at 50% initial moisture dried to 0%.

Certified in accordance with ISO 9001 and ISO 14001 and approved IP X4.

Electrical connections*			T4190
Heating Voltage			
El.	230-240V 1AC 50/60 Hz	kW (A)	6.3 (35)
	208-240V 3AC 60 Hz	kW (A)	6.3 (20)
	230-240V 3AC 50/60 Hz	kW (A)	8.3 (25)
	400V 3NAC 50/60 Hz	kW (A)	6.3 (10)
	400V 3NAC 50/60 Hz	kW (A)	8.3 (16)
Gas	230-240V 1AC 50/60 Hz	kW (A)	0.25 (10)
	208-240V 3AC 60 Hz	kW (A)	0.25 (10)
	230-240V 3AC 50/60 Hz	kW (A)	0.25 (10)
	400V 3NAC 50/60 Hz	kW (A)	0.25 (10)
Gas and air connections			
Gas	ISO 7/1-R		1/2"
Gas pressure	Natural gas	Pa	2000
		mbar	20
	Propane	Pa	2800-5000
		mbar	30
Air outlet		ø mm	125
Evacuated air	6 kW	m ³ /h	270
	8 kW		290
Pressure drop	6 kW	Max. Pa	380
	8 kW		350
Sound levels			
Airborne sound level			
L _w		dB(A)	<68
Heat emission			
% of installed power, max			15
Shipping data			
		net, kg	103
		crated, kg	114
		crated, m ³	0.8
Dimensions in mm			
A	Width		720
B	Depth		745
C	Height		1130
D			420
E			110
F			120
G			960
H			45
I			55
K			575
L			80
M			1445
1	Door opening ø 400		4 Central payment connection
2	Electrical connection		5 Gas connection
3	Exhaust connection		

* Other voltages available, see installation manual.

